

Thrust screws with fixed T-bar, DIN 6304

Item description/product images




Description

Material:
Steel.

Version:
Black oxidised. Thrust pin hardened.

Note:
For fixed spindles, the spindle is press fitted.

Drawings



Overview of items

Order No.	Version 1	D1	D2	D3	D4	L1	L2	L3	L5	Z2	min. α
B0130.106X40	fixed T-bar	M6	12	5	4,5	40	10	50	30	6	7°
B0130.106X50	fixed T-bar	M6	12	5	4,5	50	10	50	40	6	7°
B0130.108X50	fixed T-bar	M8	14	6	6	50	12	60	35	7,5	4°
B0130.108X60	fixed T-bar	M8	14	6	6	60	12	60	45	7,5	4°
B0130.110X60	fixed T-bar	M10	18	8	8	60	14	80	40	9	3°
B0130.110X70	fixed T-bar	M10	18	8	8	70	14	80	50	9	3°
B0130.112X70	fixed T-bar	M12	20	10	8	70	18	100	50	10	3°
B0130.112X80	fixed T-bar	M12	20	10	8	80	18	100	60	10	3°
B0130.116X75	fixed T-bar	M16	24	12	12	75	20	120	55	12	5°
B0130.116X90	fixed T-bar	M16	24	12	12	90	20	120	70	12	5°
B0130.116X110	fixed T-bar	M16	24	12	12	110	20	120	90	12	5°
B0130.120X75	fixed T-bar	M20	30	16	15,5	75	28	140	55	14	4°
B0130.120X90	fixed T-bar	M20	30	16	15,5	90	28	140	70	14	4°
B0130.120X110	fixed T-bar	M20	30	16	15,5	110	28	140	90	14	4°

Thrust screws with fixed T-bar, DIN 6304

Overview of items
